

SECTION 6.0

TOWING SPECIFICATIONS

TOWING GUIDELINES

Your **Sto-Away** Power Crane comes with a standard Class 3 receiver hitch, which complies with safety specifications and requirements for connection devices and towing systems for S.A.E. J684 OF MAY 87, and VESC Regulation V-5.

WARNING: By towing a trailer you change the handling characteristics of the vehicle. Conditions you may encounter can cause sudden trailer sway. When installed properly your Sto-Away Power Crane class 3 receiver hitch will not induce any of these conditions.

All SR series of **STO-AWAY** Power Bumper Cranes are equipped standard with a receiver hitch. The SR 2A, SR 3, & SR 4 have a Class 2- 3,500 lb. Pull / 300 lb. tongue weight, The SR 2B, SR2C, SR5A, SR 5T, SR6A, & SR6T have a Class 3- 5,000 lb. pull / 500 lb. tongue weight and the SR5A, SR 5T, SR6A, & SR6T can be upgraded by the up-fitter to a Class 4 (Call Factory for details), The SR7 & SR 8 have a Class 4 - 12,000 lb. pull / 1,200 lb. tongue weight. The optional face plate pintle mount can be added to the SR5A, SR5T, SR6A, SR6T, SR7 & SR8 which is a class 4 receiver hitch 12,000 lb. pull / 1,200 lb. tongue weight rating for all trailers with a GVWR over 5,000 lb. but not exceeding 12,000 lb. GVWR, when the pintle hook is properly bolted to the **STO-AWAY** per pintle hook manufacturer specifications.

WARNING: MAKE SURE YOU COMPLETELY REVIEW BOTH THE VEHICLE & TRAILER MANUFACTURERS TOWING SPECIFICATIONS.

REMEMBER: TOWING WITH THE STO-AWAY IS ONLY AS GOOD AS THE INSTALLATION OF THE STO-AWAY.